





Dimensions



Dimensions



Technical Data

Model	IPS-A22-212L IPS-A22-212N	IPS-A22-222L IPS-A22-222N
<b>General specifications</b>		
Switching Output	PNP, N/O PNP, N/C	NPN, N/O NPN, N/C
Rated Operating Distance	$S_n$ 5mm ± 10%	5mm ± 10%
Installation	Flush	Flush
<b>Nominal Ratings</b>		
Supply Voltage	$U_e$ 10-30 Vdc	10-30 Vdc
Frequency of Operating cycle	$f$ 500 Hz	500 HZ
Hysteresis/Differential travel	$H$ ±10%	±10%
Rated operating current	$I_e$ 200 mA	200 mA
No-load supply current	$I_o$ < 15 mA	< 15 mA
Voltage drop	$U_d$ < 2.2Vdc	< 2.2Vdc
OFF state current	$I_r$ < 0.1mA	< 0.1mA
Rated insulation voltage	$U_i$ 75 Vdc	75 Vdc
Utilization category	DC-13	DC-13
Repeatability/ Repeat accuracy	$R$ 0.2 mm	0.2 mm
Protection Circuit	Short circuit & Polarity reversal	Short circuit & Polarity reversal
Function Indication	LED	LED
<b>Ambient Conditions</b>		
Operating temperature	-25° C to +70° C	-25° C to +70° C
<b>Mechanical Specifications</b>		
Connection Type	Cable PVC,3 Core,-3 mtrs	Cable PVC,3 Core-3 mtrs
Core cross section	22 AWG	22 AWG
Housing material	CuZn-Nickel Plated	CuZn-Nickel Plated
Sensing face	Plastic ABS-Grey Color	Plastic ABS-Green Color
Degree of protection	IP67	IP67
<b>Compliance with Standards and Directives</b>		
Standards Conformity	EN 60947- 5-2	EN 60947- 5-2
Approval	CE	CE